

TRANSFORCE™ HT3

COMMERCIAL HIGHWAY



FOR TACKLING THE TASK AHEAD. AGAIN AND AGAIN.

Features & Benefits



Long-lasting, reliable wear



Dependable wet traction, even when loaded



Wear-Resistant Tread Compound

with a robust pattern design to help provide resistance to irregular wear.

Tread Pattern

designed to efficiently evacuate water and maintain stiffness while hauling a load for dependable performance.

Upper Sidewall Blocks

to provide additional durability.

Firestone

TRANSFORCE™ HT3



Top Fitments

- Dodge Ram 3500
- Chevrolet Silverado 2500
- Ford F-250 XL
- Ford E-250

Warranty†

- Gold Pledge Limited Warranty
- 90-Day Buy & Try™ Guarantee



Scan to discover more



Tire Specifications

| Tire Size and Service Description | Load Range | Item Number | Sidewall Styling | Approved Rim Widths | Measuring Rim Widths | Overall Tire Diameter | Overall Section Width | Tread Depth (32nd) | Revs Per Mile | UTQG | Wt. |
|-----------------------------------|------------|-------------|------------------|---------------------|----------------------|-----------------------|-----------------------|--------------------|---------------|------|-----|
| 16" Rim Diameter | | | | | | | | | | | |
| LT215/85R16 115/112R | E | 013891 | BW | 5.5-7.0 | - | 30.6 | 8.5 | 13 | - | - | 38 |
| LT235/85R16 120/116R | E | 013892 | BW | 6.0-7.5 | 6.5 | 31.7 | 9.3 | 14 | 656 | - | 48 |
| LT225/75R16 115/112R | E | 013886 | BW | 6.0-7.0 | 6.0 | 29.3 | 8.8 | 13 | 711 | - | 37 |
| LT245/75R16 120/116R | E | 013887 | BW | 6.5-8.0 | 7.0 | 30.5 | 9.8 | 14 | 684 | - | 42 |
| 17" Rim Diameter | | | | | | | | | | | |
| LT235/80R17 120/117R | E | 013893 | BW | 6.0-7.5 | - | 31.8 | 9.3 | 14 | - | - | 42 |
| LT245/75R17 121/118R | E | 013889 | BW | 6.5-7.5 | 7.0 | 31.5 | 9.8 | 14 | 661 | - | 48 |
| LT245/70R17 119/116R | E | 013898 | BW | 6.5-8.0 | 7.0 | 30.6 | 9.8 | 14 | 682 | - | 44 |
| LT265/70R17 123/120R | E | 013894 | BW | 7.0-8.5 | 8.0 | 31.7 | 10.7 | 15 | 658 | - | 45 |
| LT285/70R17 126/123R | E | 013896 | BW | 7.5-9.0 | 8.5 | 32.8 | 11.5 | 15 | 636 | - | 50 |
| 18" Rim Diameter | | | | | | | | | | | |
| LT265/70R18 124/121R | E | 013885 | BW | 7.0-9.0 | - | 32.6 | 10.7 | 15 | - | - | 47 |
| LT275/70R18 125/122S | E | 013901 | BW | 7.0-9.0 | 8.0 | 33.2 | 11.0 | 15 | 627 | - | 49 |
| LT275/65R18 123/120S | E | 013900 | BW | 7.5-9.0 | 8.0 | 32.1 | 11.0 | 15 | 649 | - | 45 |
| 20" Rim Diameter | | | | | | | | | | | |
| LT275/65R20 126/123S | E | 013899 | BW | 7.5-9.5 | - | 34.1 | 11.0 | 15 | - | - | 50 |
| LT265/60R20 121/118S | E | 013902 | BW | 7.5-9.5 | - | 32.5 | 10.7 | 15 | - | - | 48 |
| LT285/60R20 125/122R | E | 013897 | BW | 8.0-10.0 | 8.5 | 33.5 | 11.5 | 15 | 623 | - | 50 |

Tire Specifications Legend

New sizes

| | | |
|----------------------------|-----------------------------|-------------------------------|
| * OEM Tire | OWL Outline White Letter | ~ Pinned for #12 Stud Sizes |
| ¥ MOE (Mercedes Exclusive) | RBL Raised Black Letter | f Pinned for #15 Stud Sizes |
| ^ RFT (Run Flat Tire) | XL Extra Load (XL) | ** Pinned for #16 Stud Sizes |
| BW Blackwall | ◆ Pinned for #11 Stud Sizes | *** Pinned for #17 Stud Sizes |